

CERAMIC PILOT 2.0

Low consumption water softener

- **Low consumption of salt and water.**
- For homes with up to **2 bathrooms and a maximum of 5 people***.
- **High performance resins:** Greater flow and maximum efficiency.
- More compact equipment.
- **Counter-current** volumetric regeneration.



It is recommended to install Sediment Filter 50 microns 1"

REFERENCE: GS57PIL12
EAN: 8436023846134

Technical data

Weight	24 kg
Volume of resin	12 L
Resin type	Cationic strong High flow
Maximum flow	2,000 L/h
Maximum hardness	70hf°
Inlet pressure (min – max)	2 - 5 bar
Temperature	5 - 45°C
Electric consumption	6W
Electrical power supply	240 V / 50 - 60 Hz Output: DC 12 V / 1.5 A
Tank of salt capacity	35 kg
Consumption of salt per regeneration	1.8 kg*
Water consumption per regeneration	60 L *
Connections	3/4

* Values according to pressure, temperature and quality of the water to treat.

Recommended maintenance

RESIN: The resin inside the tank should be changed after approximately 8 - 10 years*.

SALT: Check the level once a month*. It is important that the equipment never runs out of salt.

SANITISOFT: A resin cleaning is recommended for each full load of salt (30 kg).


Includes

- Water Softener
- Manual
- By-pass
- Safety buoy
- Transformer

Presentation

- 1 unit (package)
- 7 units (1 pallet)

Dimensions



Ceramic Pilot 2.0:

- A: 59,8 cm
- B: 47 cm
- C: 32 cm

Packaging:

- A: 65 cm
- B: 51,5 cm
- C: 34 cm



IMPORTANT: This equipment must be installed in bacteriologically potable water.