

CERAMIC PILOT 2.5

Low consumption water softener

- **Low consumption of salt and water.**
- For homes with up to **4 bathrooms and a maximum of 8 people***.
- More compact equipment.
- **Counter-current** volumetric regeneration.



It is recommended to install a 50 micron 1" Sediment Filter

REFERENCE:GS57PIL25
EAN: 8436023846127

Technical data

Weight	41 kg
Volume of resin	25 L
Resin type	Cationic strong High flow
Maximum flow	2.5000 L/h
Maximum hardness	125hfº
Inlet pressure (min – max)	2 - 5 bar
Temperature	5 - 45°C
Electric consumption	6W
Electrical power supply	240 V / 50 - 60 Hz Output: DC 12 V / 1.5 A
Tank of salt capacity	35 kg
Consumption of salt per regeneration	3.75 kg*
Water consumption per regeneration	125 L *
Connections	3/4

* Values according to pressure, temperature and quality of the water to treat.

Recommended maintenance

RESIN: The resin inside the tank should be changed after approximately 8 - 10 years*.

SALT: Check the level once a month*. It is important that the equipment never runs out of salt.

SANITISOFT: A resin cleaning is recommended for each full load of salt (50 kg).

Includes

- Softener
- Manual
- By-pass
- Safety buoy
- Transformer

Presentation:

- 1 unit (1 package)
- 7 units (1 pallet)

Dimensions



Ceramic Pilot 2.5:
A: 105.5cm
B: 47cm
C: 32cm

Packaging:
A: 111cm
B: 51.5cm
C: 34cm



IMPORTANT: This equipment must be installed in bacteriologically potable water.